## AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application.

## Listing of Claims:

Claim 1 (Currently Amended): A routing device comprising:

a plurality of interface modules to communicate data packets using a network; and a router module coupled to each of the plurality of interface modules,

wherein the router module receives the data packets from the plurality of interface modules and to processes the data packets and to forwards the data packets between the interface modules in accordance with route information associated with the network.

Claim 2 (Original): The routing device of claim 1, further comprising a midplane coupled to the plurality of interface modules and to the router module.

Claim 3 (Currently Amended): The routing device of claim 1, wherein the router module comprises:

a packet forwarding engine; and

a concentrator module coupled between the packet forwarding engine and the plurality of interface modules.

wherein that packet forwarding engine receives the packets from the plurality of interface modules by the concentrator module, selects routes for the packets, and forwards the packets to the plurality of interface modules via the concentrator module,

wherein the packet forwarding engine a system control module and at least one and the concentrator module are integrated into a single unit separate from the interface modules.

Claim 4 (Currently Amended): The routing device of claim 3, further comprising at least one memory management circuit to provide data to the concentrator module from the packets received from the plurality of interface modules.

03/02/2005 16:20

Application Number 09/851,363 Responsive to Office Action mailed December 15, 2004

Claim 5 (Original): The routing device of claim 4, further comprising a memory coupled to the concentrator module and configured to store the data provided to the concentrator module.

SHUMAKER & SIEFFERT

Claim 6 (Currently Amended): The routing device of claim 5, wherein the concentrator module assembles output bound packets from data stored in the memory and forwards the outbound packets to the plurality of interface modules memory is further configured to store data associated with an outbound packet.

Claim 7 (Currently Amended): The routing device of claim 5, wherein the concentrator module processes inbound packets received from the plurality of interface modules to remove labels from the inbound packets, and stores data from the processed inbound packets in the memory is further configured to store incoming data associated with an inbound packet.

Claim 8 (Original): The routing device of claim 5, wherein the memory comprises an SDRAM device.

Claim 9 (Currently Amended): The routing device of claim 4, wherein the memory management circuit is further configured to provide a notification to the packet forwarding engine system control module based on information extracted from an incoming data packet.

Claim 10 (Original): The routing device of claim 9, wherein the extracted information includes at least one of source address information, destination address information, source port information, and destination port information.

Claim 11 (Currently Amended): The routing device of claim 9,

wherein the packet forwarding module is configured to select the a-routes by referencing a forwarding table based on the extracted information, and

wherein the forwarding table stores the route information for forwarding data packets received from any of the plurality of interface modules.

Claim 12 (Currently Amended): The routing device of claim 11, further comprising a routing engine to store a the routing table.

Claim 13 (Currently Amended): The routing device of claim 11, further comprising a memory to store the selected route in a forwarding table.

Claim 14 (Currently Amended): The routing device of claim 11, wherein the memory management circuit is configured to forward the incoming data packet to one of the plurality of an-interface modules based on the selected route.

Claim 15 (Original): The routing device of claim 1, further comprising a redundant router module to process the data packets and to forward the data packets between the interface modules in response to malfunction of the router module.

Claim 16 (Currently Amended): A routing device comprising:

a plurality of interface cards to communicate data packets using a network;

a router module comprising a packet processing circuit, a memory management circuit, and a route lookup circuit integrated into a single module separate from the plurality of interface cards and a routing engine; and

a midplane coupled to the router module and to the plurality of interface cards.

Claim 17 (Original): The routing device of claim 16, wherein the single module comprises a single printed circuit card that interconnects the packet processing circuit, the memory management circuit, and the route lookup circuit.

Claim 18 (Original): The routing device of claim 16, further comprising a memory coupled to the packet processing circuit and configured to store incoming data.

6517351102

Claim 19 (Original): The routing device of claim 18, wherein the memory management circuit is configured to provide packet data to the packet processing circuit.

Claim 20 (Original): The routing device of claim 18, wherein the memory is further configured to store outbound data.

Claim 21 (Original): The routing device of claim 18, wherein the memory comprises an SDRAM device.

Claim 22 (Original): The routing device of claim 16, wherein the memory management circuit is configured to provide a notification to the route lookup circuit based on information extracted from an incoming data packet.

Claim 23 (Original): The routing device of claim 22, wherein the extracted information includes at least one source address information, destination address information, source port information, and destination port information.

Claim 24 (Currently Amended): The routing device of claim 22, wherein the route lookup circuit is configured to select a route by referencing a forwarding table based on the extracted information, wherein the forwarding table stores the route information for forwarding data packets received from any of the plurality of interface cards.

Claim 25 (Original): The routing device of claim 24, wherein the route lookup circuit is configured to select the route by performing a longest prefix match based on the extracted information.

Claim 26 (Currently Amended): The routing device of claim 24, further comprising a routing engine to store the a routing table.

Claim 27 (Currently Amended): The routing device of claim 24, further comprising a memory to store the selected route in the a forwarding table.

Claim 28 (Original): The routing device of claim 24, wherein the memory management circuit is configured to forward the incoming data packet to an interface card based on the selected route.

Claim 29 (Original): The routing device of claim 16, wherein the packet processing circuit is configured to remove an L2 header from an incoming data packet.

Claim 30 (Original): The routing device of claim 16, wherein the packet processing circuit is configured to build an L2 header for an outbound data packet.

Claim 31 (Original): The routing device of claim 16, further comprising a redundant router module to process the data packets and to forward the data packets between the interface modules in response to malfunction of the router module.

Claim 32 (Currently Amended): A routing arrangement comprising:

a crossbar arrangement; and

a plurality of routing devices coupled to the crossbar arrangement, at least one routing device comprising:

a plurality of interface modules to communicate data packets using a network; and

a router module separate from the plurality of interface modules to process the data packets and to forward the data packets between the interface modules.

Claim 33 (Original): The routing arrangement of claim 32, further comprising a midplane coupled to the plurality of interface modules and to the router module.

Claim 34 (Currently Amended): The routing arrangement of claim 32, wherein the router module comprises a system control module and at least one concentrator module integrated into a single unit separate from the interface modules.

Claim 35 (Original): The routing arrangement of claim 34, further comprising at least one memory management circuit to provide data to the concentrator module.

Claim 36 (Original): The routing arrangement of claim 35, further comprising a memory coupled to the concentrator module and configured to store the data provided to the concentrator module.

Claim 37 (Original): The routing arrangement of claim 36, wherein the memory is further configured to store outbound data.

Claim 38 (Original): The routing arrangement of claim 36, wherein the memory is further configured to store incoming data.

Claim 39 (Original): The routing arrangement of claim 36, wherein the memory comprises an SDRAM device.

Claim 40 (Original): The routing arrangement of claim 35, wherein the memory management circuit is further configured to provide a notification to the system control module based on information extracted from an incoming data packet.

Claim 41 (Original): The routing arrangement of claim 40, wherein the extracted information includes at least one of source address information, destination address information, source port information, and destination port information.

Claim 42 (Currently Amended): The routing arrangement of claim 40, wherein the system control module is configured to select a route by referencing a forwarding table based on the extracted information, wherein the forwarding table stores the route information for forwarding data packets received from any the plurality of interface modules.

Claim 43 (Currently Amended): The routing arrangement of claim 42, further comprising a routing engine to store a the routing table.

Claim 44 (Currently Amended): The routing arrangement of claim 42, further comprising a memory to store the selected route in the a forwarding table.

Claim 45 (Original): The routing arrangement of claim 42, wherein the memory management circuit is configured to forward the incoming data packet to an interface module based on the selected route.

Claim 46 (Original): The routing arrangement of claim 32, further comprising a redundant router module to process the data packets and to forward the data packets between the interface modules in response to malfunction of the router module.

Claim 47 (Currently Amended): A routing arrangement comprising:

- a crossbar arrangement; and
- a plurality of routing devices coupled to the crossbar arrangement, at least one routing device comprising:
  - a plurality of interface cards to communicate data packets using a network,
- a router module comprising a packet processing circuit, a memory management circuit, and a route lookup circuit integrated into a single module <u>separate from the plurality of interface cards</u> and a routing engine, and
  - a midplane coupled to the router module and to the plurality of interface cards.

Claim 48 (Original): The routing arrangement of claim 47, wherein the single module comprises a single printed circuit card that interconnects the packet processing circuit, the memory management circuit, and the route lookup circuit.

Claim 49 (Original): The routing arrangement of claim 47, further comprising a memory coupled to the packet processing circuit and configured to store incoming data.

Claim 50 (Original): The routing arrangement of claim 49, wherein the memory management circuit is configured to provide packet data to the packet processing circuit.

Claim 51 (Original): The routing arrangement of claim 49, wherein the memory is further configured to store outbound data.

Claim 52 (Original): The routing arrangement of claim 49, wherein the memory comprises an SDRAM device.

Claim 53 (Original): The routing arrangement of claim 47, wherein the memory management circuit is configured to provide a notification to the route lookup circuit based on information extracted from an incoming data packet.

Claim 54 (Original): The routing arrangement of claim 53, wherein the extracted information includes at least one of source address information, destination address information, source port information, and destination port information.

Claim 55 (Currently Amended): The routing arrangement of claim 53, wherein the route lookup circuit is configured to select a route by referencing a forwarding table based on the extracted information, wherein the forwarding table stores the route information for forwarding data packets received from any of the plurality of interface cards.

Claim 56 (Original): The routing arrangement of claim 55, wherein the route lookup circuit is configured to select the route by performing a longest prefix match based on the extracted information.

Claim 57 (Original): The routing arrangement of claim 55, further comprising a routing engine to store a routing table.

Claim 58 (Currently Amended): The routing arrangement of claim 55, further comprising a memory to store the selected route in a the forwarding table.

Claim 59 (Original): The routing arrangement of claim 55, wherein the memory management circuit is configured to forward the incoming data packet to an interface card based on the selected route.

Claim 60 (Original): The routing arrangement of claim 47, wherein the packet processing circuit is configured to remove an L2 header from an incoming data packet.

Claim 61 (Original): The routing arrangement of claim 47, wherein the packet processing circuit is configured to build an L2 header and rewrite an L3 header for an outbound data packet.

Claim 62 (Original): The routing arrangement of claim 47, further comprising a redundant router module to process the data packets and to forward the data packets between the interface modules in response to malfunction of the router module.

Claim 63 (Currently Amended): A router comprising one hardware board integrally housing an interface concentrator that provides electrical interfaces to receive incoming packets from a plurality of interface cards, a packet processing circuit, a memory management circuit, and a route lookup circuit to select routes for the incoming packets received from the plurality of interface cards.

03/02/2005 16:20

Application Number 09/851,363 Responsive to Office Action mailed December 15, 2004

Claim 64 (Original): The router of claim 63, wherein the memory management circuit is configured to provide incoming data to the packet processing circuit.

Claim 65 (Currently Amended): The router of claim 63, wherein the memory management circuit is configured to provide a notification to the route lookup circuit based on information extracted from the an incoming data packets.

Claim 66 (Currently Amended): The router of claim 65, wherein the extracted information includes at least one of source address information, destination address information, source port information, and destination port information for each of the incoming packets.

Claim 67 (Currently Amended): The router of claim 65, wherein the route lookup circuit is configured to select the a routes by referencing a forwarding table based on the extracted information, wherein the forwarding table stores the route information for forwarding data packets received from any of the plurality of interface cards.

Claim 68 (Original): The router of claim 67, wherein the route lookup circuit is configured to select the route by performing a longest prefix match based on the extracted information.

Claim 69 (Original): The router of claim 63, wherein the packet processing circuit is configured to remove an L2 header from an incoming data packet.

Claim 70 (Original): The router of claim 63, wherein the packet processing circuit is configured to build an L2 header and rewrite an L3 header for an outbound data packet.

Claim 71 (Currently Amended): A method of manufacturing a routing device, the method comprising:

providing a plurality of interface modules to communicate data packets using a network; and

coupling the plurality of interface modules to a <u>single</u> router module to process the data packets and to forward the data packets between the interface modules.

Claim 72 (Original): The method of claim 71, further comprising coupling a midplane to the plurality of interface modules and to the router module.

Claim 73 (Currently Amended): The method of claim 71, wherein the router module comprises a system control module and at least one concentrator module integrated into a single unit separate from the interface modules.

Claim 74 (Original): The method of claim 73, further comprising providing at least one memory management circuit to provide data to the concentrator module.

Claim 75 (Original): The method of claim 74, further comprising:

coupling a memory to the concentrator module; and

configuring the memory to store the data provided to the concentrator module.

Claim 76 (Original): The method of claim 75, further comprising configuring the memory to store data associated with at least one of an outbound packet and an inbound packet.

Claim 77 (Original): The method of claim 74, further comprising configuring the memory management circuit to provide a notification to the system control module based on information extracted from an incoming data packet.

and

Application Number 09/851,363
Responsive to Office Action mailed December 15, 2004

Claim 78 (Currently Amended): The method of claim 77, further comprising configuring the system control module to select a route by referencing a forwarding table based on the extracted information, wherein the forwarding table stores the route information for forwarding data packets received from any the plurality of interface modules.

Claim 79 (Original): The method of claim 78, further comprising configuring a routing engine to store the routing table.

Claim 80 (Original): The method of claim 71, further comprising configuring a redundant router module to process the data packets and to forward the data packets between the interface modules in response to malfunction of the router module.

Claim 81 (Currently Amended): A method of manufacturing a routing device, the method comprising:

providing a plurality of interface cards to communicate data packets using a network; providing a routing module separate from the plurality of interface cards;

coupling the a-router module comprising a packet processing circuit, a memory management circuit, and a route lookup circuit integrated into a single module to the plurality of interface cards via a midplane.

Claim 82 (Currently Amended): A method of manufacturing a routing arrangement, the method comprising:

providing a crossbar arrangement; and

coupling a plurality of routing devices to the crossbar arrangement, at least one routing device comprising:

a plurality of interface modules to communicate data packets using a network; and

a router module <u>separate from the plurality of interface cards</u> to process the data packets and to forward the data packets between the interface modules.

Claim 83 (Currently Amended): A method of manufacturing a routing arrangement, the method comprising:

providing a crossbar arrangement; and

coupling a plurality of routing devices to the crossbar arrangement, at least one routing device comprising:

a plurality of interface cards to communicate data packets using a network,
a router module comprising a packet processing circuit, a memory management
circuit, and a route lookup circuit integrated into a single module separate from the plurality of
interface cards, and

a midplane coupled to the router module and to the plurality of interface cards.

Claim 84 (Currently Amended): A routing arrangement comprising:

a plurality of routing devices coupled to in a the crossbar arrangement, at least one routing device comprising:

a plurality of interface modules to communicate data packets using a network; and

a router module to process the data packets and to forward the data packets between received from any of the interface modules in accordance with route information associated with the network; and

a switch arrangement coupled to the plurality of routing devices and configured to switch control from a first routing device to a second routing device.

Claim 85 (Currently Amended): A routing arrangement comprising:

a plurality of routing devices coupled in a to the crossbar arrangement, at least one routing device comprising:

a plurality of interface cards to communicate data packets using a network,
a router module comprising a packet processing circuit, a memory management
circuit, and a route lookup circuit integrated into a single module separate from the plurality of
interface cards and a routing engine, and

a midplane coupled to the router module and to the plurality of interface cards; and

a switch arrangement coupled to the plurality of routing devices and configured to switch control from a first routing device to a second routing device.